

Medi@link *IXUSS ONE*

High-end Open-Source
Smart TV Player @ Linux

Medi@link digital Quality at Environment in Mind
with ECO Friendly Materials



1W Stand-by
Energy-saver
Energie sparer



“To meet your Expectation beyond our Competiton”



TV



MOVIE



MUSIC



PHOTO



WEB



YOUTUBE



CALENDAR



GAME

FEATURES

- 400MHz MIPS Dual Core Processor
- 512MByte RAM
- 4MByte NOR, 128MByte NAND Flash
- Linux Open-Source : Standard Linux API
- Downloadable Plug-in support
- Variable SKIN support
- WEB-interface, WEB Remote-control
- MPEG2 / H.264 Hardware Decoding
- Media Player
- S/PDIF Digital bit stream by Optical
- Unlimit Channel list on TV / Radio
- Universal Remocon (STB, TV, DVD, VCR)
- VFD display
- Firmware upgrade via network or USB
- SAMSUNG Tuner
- 1 Card reader
- HDMI Cable



www.IXUSS.info

Medi@link *IXUSS ONE*

High-end Open-Source
Smart TV Player @ Linux

TECHNICAL SPECIFICATIONS

IF / TUNERS

DVB-S2 TUNER	SAMSUNG Tuner
Input Frequency	950 ~ 2150Mhz
FEC Decoder	DVB-S2 QPSK : 1/2, 3/5, 2/3, 3/4, 4/5, 5/6, 8/9, 9/10, AUTO DVB-S2 8PSK : 3/5, 2/3, 3/4, 5/6, 8/9, 9/10, AUTO
Demodulation	DVB-S/2, QPSK, 8PSK
Input Impedence	75Ω
Input Connector	F-type, IEC 169-24, FEMALE x2
Symbol Rate	1~45MSPS
LNB POWER & Polarization	Vertical : 14V Horizontal : 19V
DiSEqC Control	Version 1.0, 1.1, 1.2, USALS Compatible

Front & Rear Panel I/O

Rear Panel I/O	Composite (CVBS) x 1 Component (YPbPr) x 1 Optical S/PDIF x 1 USB 2.0 x 2 HDMI x 1 RJ45 x 1 Smart Card x 1 Power Switch x 1
Display	VFD Display
Front Panel I/O	IR Module (38KHz)

PHYSICAL SPECIFICATIONS

Dimension	228 x 150 x 50(mm)
Gross Weight	1.43 kg
Net Weight	0.55 kg
Power Supply	
Input :	100Vac ~ 240Vac 50/60Hz 0.8A Max
Output :	DC 12V = 3.5A Max
Operating Temperature	0 °C ~ 60 °C
Storage Temperature	-10°C ~ +70°C
Power Consumption (Standby)	Max. 42W (1W)

VIDEO / AUDIO DECODING

Video Decoding	MPEG2 SD/HD, MPEG4 P10 H.264/AVC SD/HD Xvid, MKV
Audio Decoding	MPEG Audio, WAV, AIFF, WMA
Resolution	480i / 480p / 576i / 576p / 720p / 1080i / 1080p (30Hz)
Subtitles	SRT, SMI, TXT

ACCESSORIES

HDMI Cable
Power Adaptor
User Manual
Universal Remocon & User Guide



Universal remocon for STB, TV, DVD, VCR